

LEAVE ORDINARY BEHIND



**Superior cooling
products from
the world's best**



Environmental friendly cooling solutions

*with blue chip customers.

www.frigoglass.com

Designed for local market with global expertise



An innovative product lineup and are the strategic partner to world's top brands. Frigoglass is one the of top European brands operating from 10 production plants serving customers in more than 100 countries globally. Since its launch in India in 1998, Frigoglass has made rapid strides and is one of the leading manufacturer of commercial appliances serving brands ranging from beverages to breweries to dairies, to frozen foods and more.

All this supported by state of art manufacturing facilities, research labs and ably assisted by well-trained network of sales and service personnel's throughout the country.

Committed to provide environmentally friendly product solutions which enables its customers to meet with ambitious sustainability and carbon emission targets, Frigoglass all set to be a partner in progress towards the growth of Indian market.



**R&D CENTRE
ACCREDITED**
BY COKE AND PEPSI



**GLOBAL
STANDARDISED**
PRODUCTION PROCESS



**CLIMATE
CONTROLLED**
LQC



ISO9001/14001/SA8000 . LABS ISO 17025/CC CERTIFIED

OUR PARTNERS IN PROGRESS:



And many more...

www.frigoglass.com

Visi Coolers



Specifications	VG1D 295 [R134a]	VG1D 370 [R134a]	VG1D 450 [R134a]	VG1D 600 [R134a]	VG2D 1000 [R134a]
External product dimensions (W x D x H) mm	576 x 650 x 1454	576 x 650 x 1724	576 x 650 x 2055	739 x 650 x 2063	1025 x 745 x 2031
Gross Volume (lt)	294	369	462	613	975
Cooler Foot print Area (m2)	0.43	0.43	0.43	0.55	0.9
Net Weight (Kg)	71	81	96	108	171
No. of Shelves	4	5	5	5	10
Facings per shelf (500ml PET)	7	7	7	9	14
Max loading Capacity (500ml PET)	175	231	280	340	560
Climate Class	Build for tropical climates, tested at 41 Deg C / 75% RH ambient				
Full truck loading (32ft truck)	45	45	45	39	24



Specifications	VG-200 [R134a]	VG-250 [R290]	VG-550 [R134a]	VG-650 [R134a]
External product dimensions (W x D x H) mm	450 x 539 x 1464	450 x 539 x 1724	620 x 676 x 1897	620 x 676 x 2017
Gross Volume (lt)	193	237	500	538
Cooler Foot print Area (m2)	0.23	0.23	0.41	0.41
Net Weight (Kg)	53	61	97	100
No. of Shelves	4	5	6	7
Facings per shelf (500ml PET)	5	5	8	8
Max loading Capacity (500ml PET)	110	140	328	392
Climate Class	Build for tropical climates, tested at 41 Deg C / 75% RH ambient			
Full truck loading (32ft truck)	80	80	45	45

USP

Tall boy disruptor series

Ideal placement cooler

Optimized loading

Enhanced consumer appeal

Reduced logistic cost



TROPICAL IDEAL
FOR 43°C



EUROPEAN DESIGN
AND ENGINEERING



ANTI RODENT
PROTECTION SYSTEM



IP24



CORROSION
RESISTANT BODY



MAINTENANCE
FREE CONDENSER



ALL COMPONENTS
SAFETY CERTIFIED



HIGH ENERGY
EFFICIENCY COMPRESSOR



SOFT LOOK AND
ROBUST DESIGN

Vertical Freezer



Specifications	SLF-500 [R290]
Product Dimensions (W x D x H) mm	672 x 690 x 2046
Gross Volume (lt)	441
Foot print Area (m2)	0.43
Net Weight (Kg)	124
No. of shelves	5
Display Area (m2)	0.83
No. of Doors	1
Full truck load (32ft truck) qty.	36
Temperature range	-18 to -22 Deg C
Outer / Inner Cabinet	Powder coated steel
Door Lock	Provided
Cabin Insulation	60mm

USP

Build for tropical climates, tested at 41 Deg C / 75% RH ambient

Controlled reliable functionality with fitted in controller

Wide display area

Low maintenance condensor

Easy serviceability with quick electrical connectors and easy access components

Fast defrost in and around 2 minutes

Convertible Hard Door Freezers



Specifications	FH1D 100 CT [R600a]	FH1D 250 CT [R134a]	FH2D 350 CT [R134a]	FH2D 450 CT [R134a]	FH2D 560 CT [R290]
Product Dimensions (W x D x H) mm	550 x 585 x 780	831 x 666 x 930	1120 x 666 x 930	1402 x 666 x 930	1692 x 666 x 930
Gross Volume (lt)	95	233	341	446	556
No. of Doors	1	1	2	2	2
Full truck load (32ft truck) qty.	180	100	82	57	57
No. of baskets (Nos.)	1	1	1	1	1
Temperature range / Type	Convertible Type - For Freezer mode (-18 Deg C to -24 Deg C) and Cooler mode (0 to 10 Deg C)				
Outer / Inner Cabinet	Powder coated steel				
Door Lock	Provided				
Insulation	CFC Free, 60mm Thick				

Curved Glass Door Freezers



Specifications	FC2G 250 [R290]	FC2G 350 [R290]	FC2G 410 [R290]
Product Dimensions (W x D x H) mm	834 x 653 x 900	1034 x 653 x 900	1234 x 653 x 900
Gross Volume (lt)	250	350	410
No. of Doors	2	2	2
No. of Baskets	1	1	2
Temperature range / Type	Freezer mode (-18 to -24 Deg C)		
Door Lock	Provided		
Insulation	CFC Free, 70mm Thick		



INDIA
FRIGOGLASS INDIA PRIVATE LIMITED
 Plot No. 26-A, Sector 3, IMT Manesar,
 Gurgaon - 122050, Haryana

For business enquiries:
 Call: +91 124-4320800/+91 7428366994
 Email: Sales_india@frigoglass.com

GREECE
HEAD OFFICE FRIGOGLASS S.A.I.C.
 15, A. Metaxa Street, Kifissia 14564,
 Attens Greece
www.frigoglass.com